

MULTI-PRIME multi-surface adhesion promoter MMP2 clear - MMP3 silver

Description:

MULTI-PRIME Multi-surface adhesion promoter features a special blend of resins to promote adhesion to multiple surfaces to include plastics (PVC, GRP, PP-EPDM, PUR and ABS) and includes metals such as (Aluminium, Brass, Stainless steel) other surfaces should be tested before using. Simply apply the adhesion promoter followed by a topcoat and carry out an adhesion test.

Preparation	The substrate should be prepared in a usual manner making sure that repairs are smooth. All plastics should be sanded before adhesion promoter is applied! Sanding the plastic removes the oxidized layer and allows for better adhesion. Plastics should be baked for 30minutes at 60 degrees before applying adhesion promoter. When working on metals, ensure that the metal is not touched when sanded. Adhesion promoter should be applied within 4 hours of metal being exposed.
Mixing Ratio	Ready for use
Spray Viscosity	n/a
Number of coats	1 coat
Pot Life	n/a
Spray gun setup	1.0/1.2
Flash off time	10 minute Flash off before overcoating
Drying time	n/a
Handling	When dry

Completed on: 27/06/2020

The information on the document is provided to the best of our knowledge and as a guide only and We are not liable for any problems that may arise from using this product. We have tested all our products with each other in laboratory conditions and have passed all testing. Any faults that may arise from miss use or using with other brands is done so at your own risk.